



Tracking Operation		
Parallel	Line Regulation	$\leq 0.01\%+3mV$
	Load Regulation	$\leq 0.02\%+5mV$
Series	Line Regulation	$\leq 0.01\%+5mV$
	Load Regulation	$\leq 300mV$
Auxiliary Output (CH3)		
Line Regulation		$\leq 25mV$
Load Regulation		$\leq 25mV$
Ripple & Noise		$\leq 2.0mV_{rms}$
Display		
Voltmeter		3 digits LED display
Ammeter		3 digits LED display
Resolution		100mV/10mA
Accuracy	Voltage	$\pm(1\% \text{ reading}+2 \text{ digits})$
	current	$\pm(1\% \text{ reading}+2 \text{ digits})$
Protection		Over load and reverse polarity protections
Power Source		AC 110V/220V $\pm 10\%$ selectable, 50/60Hz
Operating Environment		0°C~40°C, $\leq 80\%$ RH
Storage Environment		-10°C~70°C, $\leq 70\%$ RH
Accessories		Power cord x1, Operation manual x1, TL-103 test leadx2
Dimension		310(D) x260(W) x160(H)mm
Weight		7.5kg



K&H MFG. CO., LTD.

5F., No. 8, Sec. 4, Ziqiang Rd., Sanchong Dist, New Taipei City 241, Taiwan (R.O.C.)

<http://www.kandh.com.tw> E-Mail: education@kandh.com.tw

Tel : 886-2-2286-0700 (Rep.) 886-2-2286-7786

Fax: 886-2-2287-3066, 886-2-2287-9704

